



# SAFELY TRANSPORT PEOPLE AND CARGO.

## THE BOBCAT BUV03S-7 PERSONNEL CARRIER

The Bobcat® BUV03S-7 personnel carrier swiftly and safely moves people and cargo to their destination. Equipped with an energy-efficient power solution and a built-in battery charger, it's an economical transportation solution for warehouses and worksites. Its spacious cargo deck and comfortable seating provide a smooth, hassle-free ride.

### 24-Volt Curtis Controller

The reliable 24-volt Curtis® controller is an industry standard, providing smooth power and energy efficiency while being easy to diagnose.

### Hour Meter & Battery Discharge Indicator (BDI)

The standard hour meter/BDI keeps track of battery charge and discharge levels at a glance, letting you know when it's time to plug in.

### Built-In Battery Charger

A built-in battery charger comes as a standard feature for convenient charging capabilities.

### Deep-Cycle Batteries

Four deep-cycle batteries provide plenty of long-lasting power.

### Spacious Cargo Deck

A large rear deck is ideal for holding tools or other cargo.

### Fold-Down Seat Backrest

A fold-down seat backrest and rear footrest create an additional passenger seat.

### Hand Park Brake

A conveniently located spring-loaded hand park brake keeps the vehicle securely motionless.

### Hand Side Rails

Hand side rails provide extra protection for the operator and passenger.

### Easily Removable Deck

An easy-to-remove deck cover requires no tools for removal.

### Comfortable Seat

A wide padded seat accommodates every operator and makes operation more comfortable.

### Headlamp

A headlamp provides optimum visibility and increased safety in dark operations.

### Soft Solid Tires

Soft solid tires provide reliable traction and a comfortable ride.

SPECIFICATIONS	BUV03S-7
Load Capacity	660 lb. (300 kg)
Towing Capacity	2200 lb. (1000 kg)
Battery Voltage	24V (217 Ah)
Battery Compartment Size	10.7 x 28.8 x 15.1 in. (273 x 734 x 385 mm)
Drive Motor Power	4.3 hp (3.2 kW)
Travel Speed: Loaded/Unloaded	8.7 mph (14.0 km/hr.) / 4.9 mph (8.0 km/hr.)
Max. Travel Distance (Single Charge)	19.9 mi (32.0 km)
Gradeability: Loaded/Unloaded	15% / 15%
Tires	Elastic Solid
Tire Size (Front/Rear)	15.0 x 4.5 x 8.0 in. (381 x 114 x 203 mm)
Wheels, Load/Caster (x=Drive)	1/2x
Tread (Rear)	26.0 in. (662 mm)
Service Weight (With Battery)	1036 lb. (470 kg)
Axle Loading: Unloaded (Front/Rear)	343 lb. (160 kg) / 683 lb. (310 kg)
Overall Height	45.2 in. (1150 mm)
Steering Handle Height	45.2 in. (1150 mm)
Seat Height	28.7 in. (730 mm)
Wheelbase	63.0 in. (1600 mm)
Overall Length	86.2 in. (2190 mm)
Overall Width	30.7 in. (780 mm)
Ground Clearance	2.5 in. (63 mm)
Outside Turning Radius	72.8 in. (1850 mm)

For more information on model details, go to [Bobcat.com](https://www.bobcat.com)

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

**DOOSAN**

Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2024 Bobcat Company. All rights reserved.



**B-3087** (04/24)  
EP-2M-0424-10011-F

**Bobcat Company**  
250 East Beaton Drive • West Fargo, ND 58078  
[Bobcat.com](https://www.bobcat.com)



**Bobcat®**

**One Tough Animal.**