



3250SS

3 1/4 yd³ HEAPED
CAPACITY



81.5" CUTTING
WIDTH



80+
REQUIRED
HORSEPOWER



SKID STEER SCRAPER

Your compact track loader just got a whole lot more valuable. The new and improved 3250SS is the second generation of skid steer scrapers from Ashland. We increased the earlier model's cut width from 72" to 81.5". This makes it a perfect fit for larger compact track loaders on the market today. Through testing and feedback, we've improved numerous features on this new machine. Greater clearance between the bowl and the leveling blade increases versatility. The

plastic gate guide reduces premature wear on the mainframe. See-through rear rack built into the scraper bowl. No matter what your site demands, the 3250SS can cut, carry, and dump up to 3 1/4 cubic yards while the integrated leveling blade handles final grading in a single pass.

EQUIPMENT FEATURES



HYDRAULICS

The 3250SS scraper retains all the functions of a full-sized scraper while taking advantage of the maneuverability of a skid steer. The entire bowl moves within the mainframe using a heavy duty actuating frame and linkage system. Allowing the operator complete blade control with one hydraulic remote. To top it all off, there is now a spring assembly 'hose saver' to keep your hydraulic connection hoses away from the skid steer.

ATTACHMENT PLATE

The universal mount skid steer plate will have no problem attaching to your power unit. The design is simple and with articulation of the guide pipe, operators will be in complete control. All the convenience of a plug-and-play setup.

BOWL

The bowl is formed from high-grade steel with a top lip to help reduce boil-over. Performing the whole process of cutting, carrying, and dumping, this bowl is built to last. Engineered for grading, stripping sod, cleaning ditches, and landscape projects.

FRAME

All Ashland frames consist of an amalgamation of plate steel and tubing. Our small-sized units have added heft where it's needed most and thrown on a standard leveling blade for finish work. Pivoting off of one point on the front end, this scraper will drive through everything.

STEEL

Ashland not only increased the thickness of steel but improved the yield strength by nearly 30%. Making this machine just as durable as the rest of the Ashland line. Including our bolt-on style blades for ease of maintenance.

WHEEL SYSTEM

With the capacity of a small wheel loader, the 3250SS transforms your skid steer into a mass mover. Standard 11L x 15 tires, heavy-duty spindles, and high-capacity 6-bolt hubs allow you to smoothly carry loads at speed over a greater distance. The wheel assembly is like no other on the market.

SPECIFICATIONS

Heaped Capacity	3.25 yd ³ (ISO 6485)
Recommended HP	80+ hp
Width of Cut	81.5"
Dump Angle	64 Degrees
Hydraulics	Pair 1/2" Couplers
Lift Cylinder	(2) 3.5" x 16" Stroke
Blade Set	(3) Corners, Center
Front Tires	(2) 11 x 15
Overall Width	101"
Overall Length	130"
Overall Height	50"
Weight	3,960 lb
Leveling Blade	Standard

**WATCH THE 3250SS
MACHINE WALK
AROUND**

