



155TS2

15.5yd³ HEAPED
CAPACITY



108.5" CUTTING
WIDTH



250-620
RECOMMENDED
HORSEPOWER



DIRECT MOUNT EJECTOR SCRAPER

With additional capacity over other agricultural earthmovers, the 155 series is the perfect match for operators with horsepower to spare. The 155TS2 was created for customers who asked for added capacity, ease of transport, and increased cutting width. Stay within budget without sacrificing all the bells and whistles. This scraper comes standard with high flotation tires, GPS- ready framework, 5 piece blade set, and a ride control hydraulic accumulator.



**DOUBLE CAPACITY TO 31 CU. YDS.
WITH A TANDEM SETUP**

EQUIPMENT FEATURES



- » High-flow sequence and counter-balance valve manifold system
- » Ball bushing in ejector cylinder
- » Steel bulkhead
- » Laser pad on cross-member
- » Viewing windows on the front gate and the ejector rack for better visibility
- » Hydraulic hose stand
- » Ejector sidewall rollers
- » Trunnion-block featuring improved grease retention
- » 16" diameter, 11/16"+ wall front pipe
- » Large 2.11 gal hydraulic accumulator plumbed within the lift cylinders provides a simple cushion ride control when transporting fully loaded scrapers over rough conditions.
- » Center stinger blade or optional serrated center blade, left and right corner blades and side router bits
- » A rear pushbar extension made tough for push loading to help you through the most challenging conditions.
- » 7/8" plow bolts
- » 5.75" Super high-capacity spindles and 14-bolt welded hubs
- » Rear Tires (2): 29.5 x 25 - Bias 28-ply
- » Industrial multi-piece split-rim
- » Tilting 31" ejector rack for top loading ease
- » Dual-plated floor
- » Arched front cross-member
- » Specialized large-based flanged wheel nuts
- » Convenient grease zerks in all hubs
- » 1-year structural warranty
- » 2-year hydraulic cylinder warranty

155TS2 SPECIFICATIONS

Heaped Capacity	15.5 yd ³ (11.9 m ³)
Recommended HP	250-620 hp (186-462 kw)
Width of Cut	108.5" (275.6 cm)
Gate Clearance	62" (157.5 cm)
Ejector Cylinder (1)	5" x 60" (127 mm x 1,524 mm)
Gate Cylinder (2)	4" x 13" (102 mm x 330 mm)
Lift Cylinder (2)	5" x 20" (127 mm x 508 mm)
Laser/GPS Bracket	Standard
Tires Std. Rear	(2) 29.5 x 25
Overall Width	120" (304.8 cm)
Overall Length	360" (914.4 cm)
Overall Height	95" (241.3 cm)
Weight Lead Config.	21,308 lb (9,665 kg)
Weight Rear Config.	20,808 lb (9,438 kg)